# HOT SPOT® COLLECTION

# PACE





### SHELL COLORS\*









Alpine

Pearl

Pebble

Tuscan Sun

### **CABINET COLORS\***







Almond

Havana

### **COVER COLORS**







Black

# LEGENDARY MASSAGE

## 24 Personalized-Control Jets

- 3 XL Directional Hydromassage jets
- 2 Directional Hydromassage jets
- · 2 Rotary Hydromassage jets
- 17 Directional Precision® jets

# **EASY WATER CARE**

Water Care System FreshWater® Salt System Ready

Filtration System 30 sq. ft., top loading

### LEADING ENERGY EFFICIENCY

**Jet Pump** Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty,

3.2 HP Breakdown Torque

**Circulation Pump** SilentFlo® 5000 Quiet Continuous Filtration No-Fault® 1,000 W / 115 V or 4,000 W / 230 V Heater Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal Cover

SIZE

**Dimensions** 6'10" x 6'10" x 33" / 208 cm x 208 cm x 84 cm

CAPACITY

**Seating Capacity** 

**Water Capacity** 300 gallons / 1,135 liters

Weight 775 lbs. / 350 kg dry; 4,150 lbs. / 1,880 kg filled\*\*

# **ADDITIONAL FEATURES**

**Smart Spa** 

Hot Spring Spas App Powered by the Connected Spa Kit

Technology\*

SmartJet™ System Included

**Water Feature** 

Included

Cover Lifters\*

CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps\*

Hot Spot Collection Step (Almond, Havana, and Storm)

**Entertainment** 

Wireless Sound System

**Control System** 

**Lighting System** 

IQ 2020® with LCD control panel

115 V / 20 amp,\*60 Hz (Includes GFCI protected power cord)

or 115 V / 30 amp\* or 230 V / 50 amp,\* 60 Hz

Interior: 10 multi-color LED points of light

Exterior: 4 multi-color LED points of light

\*Optional Accessories



**MONTHLY PRICE: \$182** 

<sup>\*</sup>Actual colors and products may vary from print representation. See dealer to verify.

<sup>\*\*</sup>Includes water and 7 adults weighing 175 lbs. each.

 $<sup>\</sup>bigstar \text{Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. \\$ 

<sup>◆</sup>G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.