HOT SPOT® COLLECTION

STRIDE





SHELL COLORS*









Alpine White

Pearl

arl Pebble

Tuscan Sun

CABINET COLORS*







Almond

Havana

Storm

COVER COLORS







Black

Chestnut

Grav

LEGENDARY MASSAGE

20 Personalized-Control Jets

- 1 XL Directional Hydromassage jet
- 1 XL Rotary Hydromassage jet
- 3 Directional Hydromassage jets
- 1 Rotary Hydromassage jet
- 14 Directional Precision® jets

EASY WATER CARE

Water Care System FreshWater® Salt System Ready

Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty,

3.2 HP Breakdown Torque

Circulation PumpSilentFlo® 5000 Quiet Continuous FiltrationHeaterNo-Fault® 1,000 W / 115 V or 4,000 W / 230 VInsulationFiberCor® Insulation; Certified to California
Energy Commission (CEC) and APSP 14
energy efficiency standards for portable spas

Cover WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions 7' x 5'5" x 29" / 213 cm x 165 cm x 74 cm

CAPACITY

Seating Capacity 3 seats

Water Capacity 225 gallons / 850 liters

Weight 570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology* Hot Spring Spas App Powered by the Connected Spa Kit

recimology

 $\textbf{Cover Lifters*} \qquad \qquad \textbf{CoverCradle} @, \textbf{CoverCradle II}, \textbf{Lift 'n Glide} @, \textbf{or UpRite} \\$

Steps*

Hot Spot Collection Step (Almond, Havana, and Storm)

Control System IQ 2020® with LCD control panel

115 V / 20 amp,*60 Hz (Includes GFCI protected power cord)

or 115 V / 30 amp $^{\bullet}$ or 230 V / 50 amp, $^{\bullet}$ 60 Hz

Lighting System Interior: 6 multi-color LED points of light

Exterior: 4 multi-color LED points of light

*Optional Accessories



^{*}Actual colors and products may vary from print representation. See dealer to verify.

^{**}Includes water and 7 adults weighing 175 lbs. each.

 $[\]bigstar \textit{Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.$

[◆]G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.